

PLC-XU87 | PLC-XU84

Brilliant Ideas for Your Business.

SANYO

- Resolution, native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- Brightness 2,500 (PLC-XU87), 2,000 (PLC-XU84) ANSI lumens
- Network integration with LAN connector (RJ45)
- WLAN USB key
- Low fan noise: 29 dB (Eco mode)
- Direct Power On/Off
- PIN Code lock
- 3 years warranty, 1 year lamp warranty



PLC-XU87 | PLC-XU84

Brilliant Ideas for Your Business.



TECHNICAL DATA	PLC-XU87	PLC-XU84
Category	Business & education	
Panel	3 x 0.63" TFT p-Si (4 : 3), microlens	
Projection Lamp	200 W UHP (LMP-106)	
Brightness ANSI lumens	2,500	2,000
Lamp Life	3,000 h (Eco mode) / 1,500 h (Normal mode)	3,000 h (Eco mode) / 2,000 h (Normal mode)
Fan Noise	29 dB (Eco mode) / 34 dB (Normal mode)	
Standard Lens	F = 1.6 – 2.5 / f = 17.7 – 28.3 mm	
Throw Distance Ratio	1.37 – 2.15 : 1	
Throw Distance	1.1 – 13.1 m (You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances.)	
Contrast Ratio	500 : 1	400 : 1
Resolution in Pixels	1,024 x 768 (XGA)	
Horizontal Resolution	600 TV lines	
Uniformity	85 %	
Bandwidth/Frequency	140 MHz, horizontal 15–100 kHz, vertical 50–100 Hz	
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N	
Connections	Input 1: DVI-I (digital/HDCP/analog) Input 2: D-Sub15 (RGB/Component/SCART-RGB) or Monitor Output Input 3: RCA (Composite), Mini DIN 4-pin (S-Video) Input 4: USB Type A for WLAN-Key Input 5: RJ45 (LAN) Audio: 2 x RCA (R/L mono) for Video in, 3.5 mm Stereo Jack for Computer Audio Output: 3.5 mm Stereo Jack (variable) Control Input 1: Mini DIN 8-pin (RS232) Control Input 2: USB type B	
Audio Function	1 W mono	
Keystone Correction	Vertical +/-20°	
Up/Down-Ratio	9 : 1 (Fixed U/D Ratio)	
HDTV Compatibility	720p/1,035i/1,080i (HDTV-compatible)	
Computer Compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA	
Zoom/Focus	1.57 x / manual	
Power Consumption/Voltage	217 W (Eco mode) / 282 W (Normal mode) / 100 – 240 V	217 W (Eco mode) / 268 W (Normal mode) / 100 – 240 V
Warranty	3 years, 1 year lamp (max. 2,000 h)	
Dimensions (W x H x D)	294.5 x 69.5 x 208 mm	
Weight	2.6 kg	
Standard Accessories	IR remote control with laser pointer and mouse function, batteries, USB cable (type A to B), DVI/D-Sub15 cable, power cable, lens cover with fastener and cord, soft carrying bag, operating manual, USB Key (POA-USB11G), PIN code label, CD-ROM for network module	
Optional Accessories	SCART-D-Sub15 cable (POA-CA-SCART), Component/D-Sub15 cable (POA-CA-COMPVGA), USB Memory Stick (POA-USB02)	
Lenses	Standard lens	



Technical specifications subject to change without notice. Date 03/2007

