

Wireless Bright XGA Installation Projector

3000 ANSI lumen, IEEE 802.11b/g

Wireless, stylish and fully packed with a great range of features suitable for standard installation, integration in AV systems, stand-alone display or connection to a LAN.



Sony's enhanced Air Shot™ (Version 2) technology enables a faster and more secure connection using the 802.11b/g standard. And is very easy to use. All wireless Air Shot™ accessories are supplied.

In addition to native XGA resolution and a high brightness of 3000 ANSI lumen - suitable for rooms with high level of ambient light - it is extremely quiet with an operating level of just 28dB.



Key Features

RS-232C

Connections include an RS-232C port for management and control of the projector.

Two RGB Inputs

Two 15-pin D-sub inputs allow for flexible connection. Input-A is for RGB or Component, Input-B is for RGB only.



Air Shot™ (Version 2)

The new VPL-CX86 comes supplied with the new improved Air Shot™ (Version 2). This new version offers the following advantages:

- 20% faster connection and transfer speed
- Wireless IEEE 802.11b/g
- High level security with WEP (Wired Equivalent Privacy) and WPA (Wi-Fi Protected Access)
- Added remote maintenance functions including E-mail alerts and IP Control using SNMP (Simple Network Management Protocol)

Sony Air Shot™ gives a choice of two connection modes:

- Simple mode: an easy 3-step set-up process
- Manual mode: configure wireless settings manually
 - Connect up to 100 PC's to one VPL-CX86
 - Display the image from one PC on up to five VPL-CX86
 - Connect to a LAN (Local Area Network) via a wireless LAN access point



Memory Stick™

Photos (JPEG, DCF), video clips (MPEG1) and Microsoft PowerPoints file saved as JPEG can be viewed directly from the projector using Memory Stick™ media*. BMP and TIFF files can be projected by converting them to JPEG files, using the supplied Projector Station for Presentation software. The VPL-CX86 has a standard size Memory Stick™ slot, compatible with Duo size and M.S. PRO. This means there is no need for a PC. Images can be controlled directly via the remote commander.

*Memory Stick™ media of over 2GB are not supported.

Additional Features



Intelligent Auto Set-up

Press the 'on' button and the projector will complete the following steps automatically, ensuring ease of operation:

- Lens protector opens automatically (which also avoids loss of the lens cap)
- Projector tilts to previously used angle
- Auto keystone correction is completed
- Auto input search occurs
- Smart Auto Pixel Alignment (APA) is completed.



Side Shot™



Direct Power On/Off

Skip the standby mode and turn on or off directly using a mains switch.



Off & Go Function

Unplug the projector immediately after use.



Control Panel Lock



Password Protection

VPL-CX86

Inputs



PrimeSupport

All Sony business projectors* come supplied with a 3-years support pack which offers unique extra services and benefits.

- 3-years support
- Free telephone helpdesk support in 5 languages
- Collection and delivery anywhere in EU, Norway or Switzerland

www.sonybiz.net/primesupport

*Excluding VPL-FX51



Optional Ceiling Mount Bracket PSS-AT3



Wireless LAN card slot

Air Shot™ Version 2 Kit (supplied)

IFU-WLM2 USB Wireless Module with Memory for PC (including Air Shot™ Version 2 software)



RM-PJP1 Remote Commander with Laser Pointer



SWU-GEG100A Wireless LAN Card for projector



The Magic of Sony 3LCD Technology

- Brighter Picture
- Higher Detail
- Natural Colour



For compatibility information with models using Air Shot™ and system requirements please visit www.sonybiz.net/projectors.

- eco info Halogenated flame retardants are not used in cabinets or in printed wiring boards.
- Lead-free solder is used for soldering.
- Polystyrene foam for the packaging cushions is not used in packaging.

Specification Table

Key Specifications	Native Resolution	XGA (1024 x 768 x 3)	
	Max Signal Input Resolution	SXGA+ (1400 x 1050)	
	Panel Type	0.79-inch p-Si TFT Sony LCD x 3	
	Projection System	3 LCD panels, 1 lens system	
	Brightness	3000 ANSI lumen	
	Contrast Ratio	350:1	
	Fan Noise	28dB	
	Weight	3.8kg	
Dimensions (w x h x d)		328 x 93 x 284 mm	
General	Standard Lens Zoom	1.2 times / Powered	
	Vertical Keystone Correction	+/- 30°	
	Horizontal Keystone Correction	Side Shot +/- 20°*	
	Lamp Type	190W UHP	
	Lamp Life (recommended replacement time)**	3000 H	
	Filter Cleaning Time	1000 H	
	Maximum Power Consumption	280W	
	Standby Power Consumption	5W	
	Body Colour		Pearl White
	Throwing Distance	Min - Max Screen Size (diagonally)	40 - 300 inch
40-inch / 1m screen		1.16 - 1.35m	
80-inch / 2m screen		2.36 - 2.74m	
100-inch / 2.5m screen		2.97 - 3.44m	
150-inch / 3.8m screen		4.47 - 5.18m	
200-inch / 5.1m screen		5.98 - 6.93m	
300-inch / 7.6m screen		9.00 - 10.42m	
Inputs	Input A	HD D-sub 15-pin RGB/Component	
	Input B	HD D-sub 15-pin RGB	
	Video	Component Video (via Input A) S-Video, Composite Video	
	Audio	2x Stereo Mini Jack 1 Shared between A/B, 1 for Video	
	HD Ready	YES	
Output	Monitor Out	HD D-sub 15-pin RGB	
	Audio	Stereo Mini Jack (variable)	
Control	Remote I/F	RS-232C, D-sub 9-pin	
	Network (via Air Slot™ v2)	E-mail, SNMP	
	USB	Up (Female)	
	USB Mouse Control	YES	
Slots	Wireless LAN	1	
	Memory Stick™	1 for Standard, PRO and DUO	
Speaker	Mono	1 x 1 Watt	
Supplied Accessories	Remote Commander	RM-PJM17	
	Cables	HD D-sub 15 pin 2m USB cable A type - B type	
	Wireless Kit	Air Shot™ Version 2 (see left)	
	Carrying Case	Soft Type	
Air Filter	For Replacement		
Optional Accessories	Lamp	LMP-C190	
	Ceiling Mount Bracket	PSS-AT3	
	USB Wireless Module with Memory for PC	IFU-WLM2	
	3 x phono ↔ 15 pin D-sub cable	SMF-402	

*The Horizontal Keystone Correction range depends on the input signal used. **These are not the guaranteed number of lamp hours, but the recommended hours after which the lamp should be replaced in order to ensure optimum picture quality.

© 2005 Sony Corporation. All rights reserved.
 Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measures are approximate.
 Sony is a registered trademark of Sony Corporation.

SONY

SONY EUROPE

www.sonybiz.net/projectors

IVOJO

MULTIMEDIA

www.ivojo.co.uk