

TOSHIBA

The right impression –

t95 tw95

2,200 ANSI-lumens
Contrast 2,000:1
XGA Resolution
tw95: Wireless



- Password protection, panel lock and userlogo capture
- 2 RGB Inputs, 1 RGB and 1 Audio-Output
- 1.6 x zoom with 30 degree vertical keystone correction
- tw95: USB reader, wireless LAN, power zoom, auto focus



* NCE2 is an improved colour optimization by Toshiba

DLP™, the DLP™-Badge are registered trademarks of Texas Instruments.

t95 tw95



Display 0.55" DMD Chip™*

Resolution XGA 1,024 x 768

Brightness 2,200 ANSI-lumens

Colour reproduction 16.7 million colours

Contrast 2,000:1

Projection format 4:3 switchable to 16:9

Lamp 210 W (TLPLW9LAMP)

Max. lamp life up to max. 2,000 hours /

up to max. 3,000 hours in ECO mode

Lens F = 2.07 - 2.64 / f = 20.5 - 32.8 mm wide angle

t95: manual zoom and focus

tw95: power zoom, auto focus

Zoom ratio 1.6 x optical zoom

Throw ratio 1.8 - 2.8 : 1

Frequencies (hor./vert.) 15 - 120 kHz / 50 - 150 Hz

Projection front, rear and ceiling

Digital keystone correction vertical +/- 30°

Picture size (diagonal) 0.76 m - 7.62 m

Projections distance 1.07 m - 11.09 m

Input signal NTSC / PAL / SECAM 480i, 480p, 576i, 576p, 720p, 1,080i, VGA / SVGA / XGA, SXGA + UXGA (compr.)

Inputs 2 x RGB (D-sub 15), S-video, composite video (RCA), 3 x audio (2 x RCA, 1 x stereo mini jack), tw95: USB Typ A

Outputs monitor (D-sub 15), audio (stereo mini jack)

Serial Interface RS-232C (mini DIN 8pin)

Power supply AC 100 - 240V, 50/60 Hz

Loudspeaker 1 W (mono)

Dimensions (W x H x D) 300 x 99 x 218 mm

Weight t95: 2.9 kg, tw95: 3.0 kg

Features user logo, password protection, key lock, NCE 2, digital resize- and black board-function, immediate shut down, ECO mode, auto V keystone correction, DDC compatible (blue terminal)

tw95: auto focus, power zoom, USB reader (type A), wireless LAN

Accessories remote control with laserpointer and batteries, owners manual (CD ROM), audio-, S-video-, RGB- and power cable, softcase,

tw95: WLAN card and software

Options spare lamp, camera c001, ceiling mount

Wireless communication (tw95) WLAN capable with WLAN card, wireless LAN (IEEE802.11b/g), 64/128 bit wep encryption



picture size (diagonal in m)	projection distance a (m)	
	min lenght (zooming max)	max lenght (zooming min)
0.76	1.07	1.75
1.02	1.45	2.35
1.52	2.19	3.55
2.03	2.93	4.74
2.54	3.67	5.93
3.81	5.53	8.92
5.08	7.38	-
6.35	9.24	-
7.62	11.09	-

Toshiba Information Systems (uk) Ltd
Projection & Display Technology
Toshiba Court · Weybridge Business Park
Addlestone Road · Weybridge
Surrey KT15 2UL