

Presentations in digital clarity

The ViewSonic® PJ556D projector delivers amazingly crisp digital images available only with a DLP projector. Weighing in at just 2.7kg with 2000 ANSI LUMENS and a 2000:1 CONTRAST RATIO (typ.), this portable projector makes it easy to give multimedia lessons in the classroom or dynamic presentations in the boardroom with dramatic effect. Advanced image processing, digital vertical keystone correction and optical zoom ensure the best possible image regardless of location. The PJ556D is flexible with MULTIPLE INPUTS AND SUPPORT FOR HD SIGNALS. Educational and business users alike will enjoy giving presentations with the PJ556D.

PJ556D

**VERSATILE, BRIGHT AND
PORTABLE PROJECTOR
WITH DLP® TECHNOLOGY**



ENGAGING LESSONS AND MEETINGS

- > **Bright in virtually any setting with 2000 lumens**
Packs 2000 ANSI lumens in just 2.7kg. It's the bright choice for mobile presenters.
- > **DLP® technology**
Stunning all-digital clarity with life-like colour, sharp graphics and outstanding video.
- > **Ultimate video source flexibility**
Connect a computer or add a video source for dynamic meetings and presentations.
- > **Easy set-up and auto-tuning**
One-touch set-up button for quick and easy synchronisation and sharp focus
- > **Advanced video features**
Motion-adaptive deinterlacer for superior video performance.
- > **Eco mode extends lamp life**
Extend the life of your lamp up to 3000 hours¹ while reducing noise output.
- > **OnView® controls for superior screen adjustability**
Screen geometry and colour adjustments can be made precisely via an easy-to-use, on-screen menu.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference™ 

PJ556D

VERSATILE, BRIGHT AND PORTABLE PROJECTOR WITH DLP TECHNOLOGY

ViewSonic®
See the difference™ 



OPTIONAL ACCESSORIES

- > Replacement lamp RLC-018
- > Hard case with wheels PRJ-HCA-001
- > Soft case with wheels and laptop bag CASE-006
- > Universal ceiling mount kit WMK-005
- > VGA to component video adapter ADPT-002
- > Wireless G Presentation Gateway WPG-100



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DLP	Type	0.55" DDR XGA DMD DLP
	Resolution	1024 x 768 XGA native, (max. 1280 x 1024 SXGA compressed)
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2 (F = 2.3–2.46/f = 19.91mm–21.36mm)
	Digital Keystone	Vertical ± 15°
DISPLAY	Size	25"–285" (0.64m–7.24m) (Diagonal)
	Throw Distance	1.0m–10.0m
	Throw Ratio	1.73–1.85:1
	Lamp	200W, 2000 hours (Eco mode 3000 hours ¹)
	Brightness	2000 ANSI lumens (typ.)
	Contrast Ratio	2000:1 (typ.)
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speaker	1 x 2 watt
INPUT SIGNAL	Video	RGB analogue, Video NTSC M, NTSC 4.43, PAL (60 M, N), SECAM, SDTV/EDTV (480i/p, 576i/p) HDTV (720p, 1080i)
	Frequency	F _H : 15-80kHz; F _V : 50–85Hz
COMPATIBILITY	PC	Analogue: VGA up to SXGA (scaled), 1024 x 768 @ 60Hz preferred
	Mac ²	Analogue: up to SXGA (scaled), 1024 x 768 @ 60Hz preferred
CONNECTOR	PC-VGA	1 x 15-pin mini D-sub
	Composite Video	1 x RCA jack
	S-Video	1 x 4-pin mini-DIN
	Component Video	15-pin mini D-sub to 3 x RCA component video adapter (optional) ³
	Audio	1 x 3.5mm stereo mini jack
	Control	1 x 9-pin D-sub RS-232
	USB	USB Typ B (for service only)
POWER	Voltage	AC 100–120/200–240V, 50/60Hz (auto switch)
	Consumption	< 250W (typ.)
CONTROLS	Basic	Stand-by, menu, input
	OSD	Displays Menu (brightness, contrast, V keystone correction, aspect ratio, blank screen, gamma, white peaking, colour temperature, user colour [RGB]), Video Menu (sharpness, saturation, tint), Display Menu (phase, tracking, H/V position), Advanced Menu (auto source select, projection [front, rear, ceiling], eco mode, high alt. mode, lamp hours, lamp reset, auto shutdown, OSD timeout, menu position, factory reset), Language Menu (English, French, German, Italian, Japanese, Korean, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese), audio (volume, mute)
OPERATING CONDITIONS	Temperature	0°C–40°C
	Humidity	10%–90% (non condensation)
NOISE LEVEL	Normal	36dB (typ.)
	Eco mode	32dB (typ.)
DIMENSIONS	(W x H x D mm)	256 x 102 x 223 (physical) 360 x 300 x 250 (packaging)
WEIGHT	Net	2.7kg
	Gross	5.7kg
REGULATIONS		CE, CB, GOST, Hygienic, UL, CUL, FCC-B, CCC, C-Tick, NOM, NEMKO, PCBC, PSB, PSE, ICES-003, Argentina TÜV/GS, EK, ECU, IRAM, Ukraine, WEEE, RoHS
OTHER		Vertical digital keystone correction, 3:2 pull down, Eco mode, high altitude setting
PACKAGE CONTENTS		DLP Projector, power cables (Europe [Schuko]/UK), VGA cable, AV cable (RCA), S-video cable, audio cable, remote control with laser pointer, batteries, lens cap, soft carrying case, Quick Start Guide (multi-language), ViewSonic Wizard CD (User guide) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm

ViewSonic Europe Limited/UK

Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom

Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Finland

ViewSonic Italy

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Sweden

Tel: +32 (0)56 85 26 27

Tel: +45 70 22 11 71

Tel: +358 20 7120 860

Tel: +39 02 73 95 50 22

Tel: +971 (0) 4 88 11 871

Tel: +31 (0)20 491 9254

Tel: +47 (0) 22 88 17 60

Tel: +34 (0) 91 63 05 339

Tel: +46 (0) 8 50 71 30 00

¹ Running Eco mode exclusively can extend lamp life up to 3000 hours. ² May require optional Mac adapter ³ Optional cables required.

Copyright © 2007 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. The DLP logo is a trademark of Texas Instruments. Corporate names and trademarks stated herein are the property of their respective companies. VS PJ556D-1 05/07-UK